



# SR320 THER SR3200

## SCHOTTKY BARRIER RECTIFIERS

Reverse Voltage - 20 to 200 Volts    Forward Current - 3.0 Ampere


### FEATURES

- \* Low forward voltage drop
- \* High current capability
- \* High reliability
- \* High surge current capability
- \* Epitaxial construction

### MECHANICAL DATA

- \* Case: Molded plastic
- \* Epoxy: UL 94V-0 rate flame retardant
- \* Lead: Axial leads, solderable per MIL-STD-202, method 208 guaranteed
- \* Polarity: Color band denotes cathode end
- \* Mounting position: Any
- \* Weight: 1.10 grams

#### DO-27



Dimensions in inches and (millimeters)

## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating 25°C ambient temperature unless otherwise specified.  
Single phase half wave, 60Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.

TYPE NUMBER	SR320	SR330	SR340	SR350	SR360	SR380	SR3100	SR3150	SR3200	UNITS
Maximum Recurrent Peak Reverse Voltage	20	30	40	50	60	80	100	150	200	V
Maximum RMS Voltage	14	21	28	35	42	56	70	105	140	V
Maximum DC Blocking Voltage	20	30	40	50	60	80	100	150	200	V
Maximum Average Forward Rectified Current	3.0									A
See Fig. 1										
Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	80									A
Maximum Instantaneous Forward Voltage at 3.0A	0.55		0.70		0.85		0.92			V
Maximum DC Reverse Current Ta=25°C	0.05									mA
at Rated DC Blocking Voltage Ta=100°C	10									mA
Typical Junction Capacitance (Note1)	250									pF
Typical Thermal Resistance RθJA (Note 2)	20				10					°C/W
Operating Temperature Range Tj	-65 — +125				-65 — +150					°C
Storage Temperature Range Tstg	-65 — +150									°C

#### NOTES:

1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.
2. Thermal Resistance Junction to Ambient Vertical PC Board Mounting 0.5"(12.7mm) Lead Length.

# RATING AND CHARACTERISTIC CURVES (SR320 THRU SR3200)

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-TYPICAL FORWARD CHARACTERISTICS




FIG.3-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.4-TYPICAL JUNCTION CAPACITANCE




FIG.5 - TYPICAL REVERSE CHARACTERISTICS

